

Setting up start_proledb when the PRONTO server starts

When the PRONTO server starts (after a reboot, for instance), it needs to read the start_proledb script in order to run the proledb program. The start-up script must be included in the S99pronto file.

To access S99pronto, you will need psd or root access.

The S99pronto file locations vary but will normally be in the **/pronto/lib** directory for AIX servers. For Linux the location can be **/etc/rc.d/rc5.d**. If you cannot find it, as the SU user (super user) in the root directory (i.e. '/'), run the following command **'find . -name S99pronto'**.

Step-by-step guide

To Add the Start-up Script to S99pronto:

1. Open up **proclient**.
2. Enter in the **'IP address'** of the Pronto box you are trying to access.
Log in to Pronto using the psd or root user and password.
 - a. After logging in if you remain in the **shell** window, type in **prospl**.
4. Navigate to the relevant company database.
5. Open up S99pronto using **vi**.
Enter the following two lines into the file:
 - a. #Run the Commerce Vision driver
 - b. su commvisi -c "/home/commvisi/start_proledb" (* replace /home/commvisi with the commvisi home directory)
7. Save the file and exit.

Below is an extract from an S99pronto file for an aix server:

```
#su root -c "$PRONTO/bin/proserver"

# Uncomment the following if PRONTO network mail is required.
#su root -c "$PRONTO/bin/promaild"

# Uncomment the following if PRONTO database mirroring is required.
#su root -c "$PRONTO/bin/procplg"

# Run the Commerce Vision driver proledb.aix
su commvisi -c "/home/commvisi/start_proledb"

# Ensure everything has started before we exit.
sleep 2
..
esac
~
~
~
```

Related articles

Content by label

There is no content with the specified labels